

WQ

National Standard
Sewage Pump

Technical parameters

Model	Power(kW)	Flow(m³/h)	Head(m)	Voltage(V)	Synchronous speed (r/min)	Caliber(mm)
WQ120-25-15	15	120	25	380	2900	150
WQ180-15-15	15	180	15	380	2900	200
WQ20-80-18.5	15	20	80	380	2900	50
WQ30-68-18.5	18.5	30	68	380	2900	65
WQ60-45-18.5	18.5	60	45	380	2900	80
WQ80-40-18.5	18.5	80	40	380	2900	100
WQ100-36-18.5	18.5	100	36	380	2900	150
WQ180-18-18.5	18.5	180	18	380	2900	200
WQ20-90-22	18.5	20	90	380	2900	50
WQ30-75-22	22	30	75	380	2900	65
WQ60-50-22	22	60	50	380	2900	80
WQ80-45-22	22	80	45	380	2900	100
WQ100-40-22	22	100	40	380	2900	150
WQ200-20-22	22	200	20	380	2900	200
WQ80-13-5.5	5.5	80	13	380	1450	80
WQ110-10-5.5	5.5	110	10	380	1450	100
WQ150-7-5.5	5.5	150	7	380	1450	150
WQ80-20-7.5	5.5	80	20	380	1450	80
WQ100-15-7.5	7.5	100	15	380	1450	100
WQ145-9-7.5	7.5	145	9	380	1450	150
WQ250-6-7.5	7.5	250	6	380	1450	200
WQ100-25-11	7.5	100	25	380	1450	100
WQ180-11-11	11	180	11	380	1450	150
WQ300-7-11	11	300	7	380	1450	200
WQ400-5-11	11	400	5	380	1450	250
WQ100-30-15	11	100	30	380	1450	100
WQ200-15-15	15	200	15	380	1450	150
WQ250-11-15	15	250	11	380	1450	200
WQ500-5-15	15	500	5	380	1450	250
WQ100-35-18.5	15	100	35	380	1450	100
WQ180-20-18.5	18.5	180	20	380	1450	150
WQ250-15-18.5	18.5	250	15	380	1450	200
WQ500-7-18.5	18.5	500	7	380	1450	250
WQ650-5-18.5	18.5	650	5	380	1450	300
WQ100-40-22	18.5	100	40	380	1450	100
WQ200-22-22	22	200	22	380	1450	150
WQ300-16-22	22	300	16	380	1450	200
WQ500-9-22	22	500	9	380	1450	250
WQ650-7-22	22	650	7	380	1450	300
WQ120-45-30	22	120	45	380	1450	100
WQ180-30-30	30	180	30	380	1450	150
WQ250-22-30	30	250	22	380	1450	200
WQ600-9-30	30	600	9	380	1450	250
WQ800-7-30	30	800	7	380	1450	300
WQ1200-4.5-30	30	1200	4.5	380	1450	350
WQ120-50-37	30	120	50	380	980	100
WQ200-35-37	37	200	35	380	1450	150
WQ300-25-37	37	300	25	380	1450	200
WQ600-12-37	37	600	12	380	1450	250
WQ800-9-37	37	800	9	380	1450	300
WQ1000-6-37	37	1000	6	380	1450	350
WQ1100-6-37	37	1100	6	380	980	350
WQ1400-5-37	37	1400	5	380	980	400
WQ100-57-45	37	100	57	380	1450	100
WQ200-40-45	45	200	40	380	1450	150
WQ300-32-45	45	300	32	380	1450	200
WQ600-15-45	45	600	15	380	1450	250

WQ

National Standard
Sewage Pump

Technical parameters

Model	Power(kW)	Flow(m³/h)	Head(m)	Voltage(V)	Synchronous speed (r/min)	Caliber(mm)
WQ800-12-45	45	800	12	380	1450	300
WQ1000-8-45	45	1000	8	380	1450	350
WQ1200-8-45	45	1200	8	380	980	350
WQ1500-6-45	45	1500	6	380	980	400
WQ100-65-55	55	100	65	380	1450	100
WQ180-50-55	55	180	50	380	1450	150
WQ300-40-55	55	300	40	380	1450	200
WQ600-20-55	55	600	20	380	1450	250
WQ800-15-55	55	800	15	380	1450	300
WQ1000-10-55	55	1000	10	380	1450	350
WQ1100-10-55	55	1100	10	380	980	350
WQ1500-8-55	55	1500	8	380	980	400
WQ2200-5-55	55	2200	5	380	980	500
WQ120-75-75	75	120	75	380	1450	100
WQ200-60-75	75	200	60	380	1450	150
WQ350-45-75	75	350	45	380	1450	200
WQ600-25-75	75	600	25	380	1450	250
WQ800-20-75	75	800	20	380	1450	300
WQ1000-15-75	75	1000	15	380	1450	350
WQ1200-15-75	75	1200	15	380	980	350
WQ1500-10-75	75	1500	10	380	980	400
WQ2000-8-75	75	2000	8	380	980	500
WQ120-85-90	90	120	85	380	1450	100
WQ200-70-90	90	200	70	380	1450	150
WQ300-55-90	90	300	55	380	1450	200
WQ600-30-90	90	600	30	380	1450	250
WQ800-25-90	90	800	25	380	1450	300
WQ1000-18-90	90	1000	18	380	1450	350
WQ1200-18-90	90	1200	18	380	980	350
WQ1500-15-90	90	1500	15	380	980	400
WQ2000-10-90	90	2000	10	380	980	500
WQ100-100-110	110	100	100	380	1450	100
WQ180-80-110	110	180	80	380	1450	150
WQ300-65-110	110	300	65	380	1450	200
WQ600-35-110	110	600	35	380	1450	250
WQ800-30-110	110	800	30	380	1450	300
WQ1000-25-110	110	1000	25	380	1450	350
WQ1300-20-110	110	1300	20	380	980	350
WQ1800-15-110	110	1800	15	380	980	400
WQ2500-10-110	110	2500	10	380	980	500
WQ3800-6-110	110	3800	6	380	980	600
WQ200-90-132	132	200	90	380	1450	150
WQ400-75-132	132	400	75	380	1450	200
WQ600-50-132	132	600	50	380	1450	250
WQ800-35-132	132	800	35	380	1450	300
WQ1100-28-132	132	1100	28	380	1450	350
WQ2000-15-132	132	2000	15	380	980	400
WQ3000-10-132	132	3000	10	380	980	500
WQ3500-8-132	132	3500	8	380	980	600
WQ250-100-160	160	250	100	380	1450	150
WQ400-85-160	160	400	85	380	1450	200
WQ600-60-160	160	600	60	380	1450	250
WQ800-40-160	160	800	40	380	1450	300
WQ1000-35-160	160	1000	35	380	1450	350
WQ2000-18-160	160	2000	18	380	980	400
WQ3000-13-160	160	3000	13	380	980	500
WQ3500-10-160	160	3500	10	380	980	600